

## LAND BASED RECORDER



### Cable-free, Radio-free, Autonomous Data Recorder

- Scalability greater than 50,000 channels
- Delivers high-resolution with a 24-bit delta-sigma ADC
- Built-in GPS receiver and disciplined clock
- Greater than 30 days of continuous recording
- Compatible with explosive, vibratory, and impulsive energy sources
- Accepts standard analog sensor inputs
- Has a built-in full-resolution test generator
- Available as 1, 2, 3, or 4 channel versions
- Has an LED Status/Deployment state indicator



## Cable-free, Radio-free Autonomous Data Recording

The GSX is designed for cable-free/radio-free seismic data recording. The self-contained unit includes 1 to 4 channels of 24-bit digitization, an integrated high sensitivity GPS receiver, built-in test signal generator, up to 32 GB per channel of non-volatile solid-state data storage, and a high-speed data port. The unit is housed in a sealed case, with an input connector and an extended life battery/data port connector.



### GSX SYSTEM TESTS

The seismic channel performance and sensor tests can be performed by the GSX System. The user can choose a partial or complete set of tests that can be run in sequence. The user can also choose to display all of the results or only the failures. In the tests described below, the system software automatically controls the Channel Input Switch Positions and Test Oscillator Settings during the tests. All tests can be run at all sample intervals and preamp gains of the GSX.

- ▲ Harmonic Distortion
- ▲ Impulse Response
- ▲ Equivalent Input Noise
- ▲ Instantaneous System Dynamic Range
- ▲ Gain Accuracy
- ▲ Common Mode Rejection
- ▲ Geophone Impedance and THD
- ▲ Crossfeed (multi-channel)

# Land Based Recorder

## Features and Specifications

- 24-bit digital recorder
- Built-in GPS and disciplined clock
- Built-in full resolution test signal generator
- Solid-state flash memory
- Scalability greater than 50,000 channels
- Greater than 30 days of continuous recording
- Compatible with vibratory, explosive, and impulsive energy sources
- LED Status/Deployment State Indicator
- Accepts standard analog sensor input
- Available as 1,2,3, or 4 channel versions
- 24-bit delta-sigma ADC
- 1 Hz to 1600 Hz freq. response
- <20  $\mu$ sec. of UTC (GPS clock)
- Up to 32 GBytes per channel flash memory storage
- External extended life battery
- Operating Temperature:  $-40^{\circ}$  C to  $+85^{\circ}$  C
- Humidity: 0 to 100%
- Selectable Gains:
  - — X1, X2, X4, X8, X16, X32, X64
  - — 0, 6, 12, 18, 24, 30, 36 dB
- Sample Intervals:
  - — .25, .5, 1, 2, 4 milliseconds

Max Input Signal:	1.80 Vrms @ 0 Gain
Total Dynamic Range:	140 dB
System Dynamic Range @ 0dB Gain:	126 dB @ 4 msec SI 124 dB @ 2 msec SI 120 dB @ 1 msec SI 117 dB @ .5 msec SI 106 dB @ .25 msec SI
Equivalent Input Noise @ 2 msec SI:	1.13 $\mu$ V @ Gain 0 dB 0.58 $\mu$ V @ Gain 6 dB 0.33 $\mu$ V @ Gain 12 dB 0.22 $\mu$ V @ Gain 18 dB 0.19 $\mu$ V @ Gain 24 dB 0.18 $\mu$ V @ Gain 30 dB 0.17 $\mu$ V @ Gain 36 dB
Input Impedance:	20 k $\Omega$ /0.06 $\mu$ f Difference Mode 205 k $\Omega$ Common Mode

System Dynamic Range @ 2 msec SI:	124 dB @ Gain 0 dB 123 dB @ Gain 6 dB 122 dB @ Gain 12 dB 120 dB @ Gain 18 dB 115 dB @ Gain 24 dB 110 dB @ Gain 30 dB 105 dB @ Gain 36 dB
Total Harmonic Distortion:	0.0005%
Common Mode Rejection:	0.001%
Gain Accuracy:	1%
Anti-Alias Filter:	Rejection @ Nyquist: 130 dB Frequency @ -3 dB: 0.83 Nyquist Linear or Minimum Phase
GPS Time Standard:	<1 ppm
Weight:	2 lbs.
Max Dimensions:	3.5"W x 3.0"H x 6.67"L

## LAND BASED RECORDER

**Big Advances in Small Packages**



GSX1 with a BN6 battery and a GS-ONE geophone in a Land Case.

7007 Pinemont Drive • Houston, Texas 77040 USA  
www.geospace.com • T: 713-986-4444 • F: 713-986-4445

**Geospace Technologies, Canada**  
2735 - 37th Avenue N.E.  
Calgary, Alberta,  
T1Y 5R8 Canada  
403 250-9600

**Geospace Technologies, China**  
Room 700, 7th Floor  
Lido Office Tower, Lido Place  
Jichang Road, Jiang Tai Road  
Beijing, 100004, P.R.China  
011 (86) 10 6437 8768

**Geospace Technologies**  
Sucursal Sudamericana  
Carrera 127-22 G 28 Int. 30  
Agrupación Industrial La Esperanza  
Bogotá, Colombia  
011-57-1-742-7414

**Geospace Technologies, Eurasia**  
Kirovogradskaya, 36  
Ufa, Baskortostan  
Russia 450001  
011 (7) 3472 25 39 73

**Geospace UK**  
F3 Bramingham Business Park,  
Enterprise Way, Luton  
Bedfordshire LU3 4BU, England  
011 44 (0) 7775 688 467