

NAVIGATOR BIRD

STREAMER DEPTH CONTROL SYSTEM



The Navigator Bird streamer depth control system enhances offshore marine acquisition survey operations through design efficiency unique to the industry. The Navigator Bird features very high lift force at low speeds, extremely low power consumption, and robust, modular mechanics for high reliability.

The Navigator Bird comes equipped with a deep-service depth transducer, a fluxgate magnetometer, and a wing angle sensor. Continuous servo action, coupled with sophisticated algorithms to predict and respond to varying conditions of towed arrays, provides unprecedented streamer depth control.

A high-torque servo motor enables the Navigator Bird to utilize a high aspect ratio wing for lifting up to 75 lbs. at 5 knots, giving operators a 60% increase in streamer control at low speeds over existing devices. Control is noticeably quicker and smoother even during low-speed deployment and retrieval. By combining time-proven mechanical advantages with advanced microprocessor control features, the Navigator Bird provides reliable depth control for a minimum of 7000 hours of uninterrupted operation.

The Navigator Bird System is easily interfaced to the primary navigation system via a network-interface using standard data format. User access can be as simple as using a standard web browser. By incorporating heading, wing angle, and temperature measurements the operator has an acquisition platform to derive critical ballast and 3D processing information.

NAVIGATOR BIRD

Features

- By utilizing hydrostatic water pressure, trim is continuous and instantaneous
- Battery is not regularly consumed for trimming
- Minimum 10 months of battery life
- 75 lbs. of lift at 5 knots
- Measures Earth's magnetic field in addition to magnetic heading
- Detection, reporting, and recording of magnetic anomalies possible

TECHNICAL SPECIFICATIONS

Maximum Operating Depth	35 m (114.863 ft.) (50.5 psig)
Maximum Depth	250 m (830 ft.) (365 psig)
Depth Accuracy	±0.15 m at 0–30 m; ±0.3 m at 30–60 m
Depth Control Stability	±0.2 m (3 to 7 knots, ±2.25 kg buoyancy) ±0.5 m (1.5 to 7 knots, ±2.25 kg buoyancy)
Depth Servo Adjustment Rate	Continuous
Action After Battery Exhaustion	Maintains servo action to last depth setting
Heading Error	±0.5° World Wide
Pitch and Roll Range	±45°
Approximate Battery Life	7000 hours
Operating Temperature Range	-5° to +50° C (23° to 122° F)
Temperature Accuracy	±3° C
Weight in Water	2.3 kg (5 lbs.)
Overall Length	107 cm (42 in.)
Wingspan	77 cm (30.4 in.)

All rights reserved. Specifications subject to change at sole discretion of Geospace Technologies.



7007 Pinemont Drive • Houston, Texas 77040 USA

www.geospace.com

Tel: 713-986-4444 • Fax: 713-986-4445



Geospace Technologies, Canada
2735 - 37th Avenue N.E.
Calgary, Alberta,
T1Y 5R8 Canada
403 250-9600

Geospace Technologies, China
Room 700, 7th Floor
Lido Office Tower, Lido Place
Jichang Road, Jiang Tai Road
Beijing, 100004, P.R.China
011 (86) 10 6437 8768

Geospace Technologies
Sucursal Sudamericana
Carrera 127-22 G 28 Int. 30
Agrupación Industrial La Esperanza
Bogotá, Colombia
011-57-1-742-7414

Geospace Technologies, Eurasia
Kirovogradskaya, 36
Ufa, Baskortostan
Russia 450001
011 (7) 3472 25 39 73

Geospace UK
F3 Bramingham Business Park,
Enterprise Way, Luton
Bedfordshire LU3 4BU, England
011 44 (0) 7775 688 467