

LHR CHARGE & DOWNLOAD DATA



Shown in 1U Rack Mount Tray

Remove drawer from the rack mount tray for desktop placement

Features:

- Rack-mountable with slide-out trays to reduce cable clutter, and store lanyards.
- Connect up to three racks to one computer to gather data from the LHRs.
- Simultaneously charge and auto-download data (with LMC software) up to seven Line Health Recorders (LHRs).

TECHNICAL SPECIFICATIONS	
Voltage Range	100–260v AC, 50–60Hz at 1.05 Amp.
Operating Temperature Range	0 to 50°C
Storage Temperature Range	-40 to +65°C
Operating Humidity	<80% RH, non-condensing
Storage Humidity	<95% RH, non-condensing
Size	1U tall (1.75") x 16" wide x 14" deep
Weight	4 lbs.

Specifications subject to change at sole discretion of Geospace Technologies.



7007 Pinemont Drive • Houston, Texas 77040 USA

www.geospace.com

Tel: 713-986-4444 • Fax: 713-986-4445



Geospace Technologies, Canada
2735 - 37th Avenue N.E.
Calgary, Alberta,
T1Y 5R8 Canada
403 250-9600

Geospace Technologies, China
Room 700, 7th Floor
Lido Office Tower, Lido Place
Jichang Road, Jiang Tai Road
Beijing, 100004, P.R.China
011 (86) 10 6437 8768

Geospace Technologies
Sucursal Sudamericana
Carrera 127-22 G 28 Int. 30
Agrupación Industrial La Esperanza
Bogotá, Colombia
011-57-1-742-7414

Geospace Technologies, Eurasia
Kirovogradskaya, 36
Ufa, Baskortostan
Russia 450001
011 (7) 3472 25 39 73

Geospace UK
F3 Bramingham Business Park,
Enterprise Way, Luton
Bedfordshire LU3 4BU, England
011 44 (0) 7775 688 467