

GSB RECORDER WITH BATTERY



Data Recorder with Internal Battery

- Continuous cable-free autonomous recording
- 24-bit resolution and 124 dB instantaneous dynamic range
- Connector for external geophone
- Battery life: 60 days @ 24 hrs/day operation
- Built-in full resolution test generator
- Solid-state flash memory: 16 or 32 GB

GSB RECORDER WITH BATTERY

MECHANICAL SPECIFICATIONS

Length x Width	16.94 x 8.89 cm	6.67 x 3.50 in.
Height	7.62 cm	3.0 in.
Weight	1.0 kg	2.2 lbs.
Operating Temperature Range	-40°C to +60°C	-40°F to +140°F

ELECTRICAL SPECIFICATIONS

Digitized 1C Recording Station:	1 Channel, 24-bit A/D Digitizer	
Digitization	24-bit Delta-Sigma	
Sample Interval	0.25, 0.5, 1, 2, 4 ms	
Pre-amplifier Gains	0, 6, 12, 18, 24, 30, 36dB	
Maximum Input Signal	1.77 Vrms	
Equivalent Input Noise (@2ms sample interval)	0.17 μ Vrms	
Gain Accuracy	Better than 1%	
Anti-alias Filter	83% Nyquist	
Instantaneous Dynamic Range	124 dB @2ms sample interval	
THD (Instrument)	0.0005%	
Flash Memory	16 or 32 GB per channel	
Frequency Response	1 Hz – 1650 Hz @ ¼ ms sample interval	
Battery Module	60 days operation	

7007 Pinemont Drive • Houston, Texas 77040 USA
www.geospace.com • T: 713-986-4444 • F: 713-986-4445

Geospace Technologies, Canada
 2735 - 37th Avenue N.E.
 Calgary, Alberta,
 T1Y 5R8 Canada
 403 250-9600

Geospace Technologies, China
 Room 700, 7th Floor
 Lido Office Tower, Lido Place
 Jichang Road, Jiang Tai Road
 Beijing, 100004, P.R.China
 011 (86) 10 6437 8768

Geospace Technologies
 Sucursal Sudamericana
 Carrera 127-22 G 28 Int. 30
 Agrupación Industrial La Esperanza
 Bogotá, Colombia
 011-57-1-742-7414

Geospace Technologies, Eurasia
 Kirovogradskaya, 36
 Ufa, Baskortostan
 Russia 450001
 011 (7) 3472 25 39 73

Geospace UK
 F3 Bramingham Business Park,
 Enterprise Way, Luton
 Bedfordshire LU3 4BU, England
 011 44 (0) 7775 688 467